



RPA 1600

RPA 2000

CAPACITY	/ KAPASİTE	tons/h	10-15 tons	25-30 tons
ROTOR LENGTH	/ ROTOR UZUNLUĞU	mm	1580	1980
ROTOR DIAMETER	/ ROTOR ÇAPI	mm	Ø 750×1580	Ø 750×1980
ROTOR RETURN SPEED	/ ROTOR DÖNÜŞ HIZI	rpm	33	33
HYDRAULIC ENGINE	/ HIDROLİK MOTOR	kw	22	30
PUMP	/ POMPA	cc	112	112
BUNKER LENGTH	/ BUNKER UZUNLUĞU	m	6	6
BUNKER VOLUME	/ BUNKER HACMİ	m ³	20	25

Bag openers working principle is based on squeezing and ripping the waste between knives located on a rotating drum and a set of movable knives. The heavy-duty chain conveyor located in the feeding section allows both dosing the material and storing material for a time interval.

Another advantage of the bag openers is, the machine does not shred the waste so, recyclable quantity does not affected by the machine . We provide bag openers in various capacities based on your demands.

Robust Rifay Design
Sağlam Rifay Tasarımı Yapı

High Corrosion Resistance
Aşınmaya Karşı Dayanıklı

Euro Standarts Safety
Avrupa Standartlarında Güvenlik

Poşet açıcılar büyük bir tambur üzerine yerleştirilmiş olan bıçakların dönmesiyle atığı döküş ağızındaki bıçaklara çarptırıp poşeti yırtması şeklinde çalışır. Besleme ağızında bulunan ağır seri konveyör sayesinde hem malzemenin sisteme düzgün beslenmesi hem de malzeme depolanmasında kullanılır.

Halilbeyli OSB. Mah.
BAYOSB Enerji Cad. No:7
Kemalpaşa İzmir/TÜRKİYE

www.rifay.com info@rifay.com



RIFAY



Turkey
Discover
the potential

Phone : +90 232 436 38 00